## English translation of excerpts of JP 2003-81733

Japanese Patent Publication A No.: 2003-81733 (P2003-81733A)

Date of Publication: March 19, 2003

Application No.: 2002-78689 (P2002-78689)

Date of Filing: March 20, 2002

Priority No.: Patent Application No. 2001-204362

(P2001-204362)

Priority Date: July 5, 2001

Priority Country: Japan (JP)

Applicant: Shiseido Co., Ltd.

component (b) is 1:9 to 4:1.

Inventors: Tomoko SATO, Tetsuya KANAMURA, Fumiaki MATSUZAKI and

Toshio HARIKI

Title of the Invention: Powder composition

## [Claims]

[Claim 1] A powder composition comprising (a) a fluorine-treated powder and (b) an oily component having a surface tension value (average) of not less than  $2.0\times10^{-2}$  N/m, without substantially containing water, which is liquefied by friction of an application thereof.

[Claim 2] The powder composition of claim 1, wherein the component (a) is a fluorine-treated powder obtained by treating the surface of a clay mineral with fluorine.

[Claim 3] The powder composition of claim 1, wherein the component (a) is a fluorine-treated powder obtained by treating the surface of a clay mineral with at least one gel selected from hydrates, partial dehydrates and anhydrides of metal hydroxides and metal salts and thereafter treating the surface treated clay mineral with fluorine.

[Claim 4] The powder composition of claim 2 or 3, wherein the clay mineral is at least one kind selected from talc, kaolin, silicic anhydride, saponite, sericite, mica and boron nitride.

[Claim 5] The powder composition of any one of claims 1 to 4, wherein the ratio (mass ratio) of the component (a) to the

[Claim 6] The powder composition of any one of claims 1 to 5 which is a powder cosmetic.

[Claim 7] The powder composition of any one of claims 1 to 5 which is a powder paint.